	<b>MATERIAL SAFETY DATASHEET</b>		Reference	FS ADSUPM in
			Date	19/01/15
			Revision	2
			Page	1 of 14
<b>Code:</b>	<b>ADSUPM</b>	<b>Denomination</b>	<b>CHEMICAL ADHESIVE CARTRIDGE</b>	

## SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE SOCIETY OR THE COMPANY.

### 1.1 Product Identifier.

Product Name: MOUNTING ADHESIVE

### 1.2 Relevant identified uses of the mixture and uses advised against.

MOUNTING ADHESIVE

### 1.3 Details of the supplier of the safety data sheet.

Company: TECNICAS EXPANSIVAS, S.L  
Address: P.I LA PORTALADA II C/ Segador Nº13  
Town: Logroño  
Province: La Rioja  
Telephone: 941 272131  
Fax: 941 272132  
E-mail: [info@indexfix.com](mailto:info@indexfix.com)

### 1.4 Emergency contact number: 941 272131 (Only available during office hours)

## SECTION 2: HAZARD IDENTIFICACION

### 2.1 Classification of the mixture.

In accordance with Directive 1999/45/EC:

F - Highly flammable.

Xi - Irritating to eyes.

Vapours may cause drowsiness and dizziness.

In accordance with Regulation (EU) No 1272/2008:

Eye Irrit. 2 : Causes serious eye irritation.

Flam. Liq. 2 : Highly flammable liquid and vapour.

STOT SE 3 : May cause drowsiness or dizziness.

### 2.2 Label elements.

#### Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:




Signal Word:

**Danger**

H statements:

H225

Highly flammable liquid and vapour.

	<b>MATERIAL SAFETY DATASHEET</b>		Reference	FS ADSUPM in
			Date	19/01/15
			Revision	2
			Page	2 of 14
<b>Code:</b>	<b>ADSUPM</b>	<b>Denomination</b>	<b>CHEMICAL ADHESIVE CARTRIDGE</b>	

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

**P statements:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground/bond container and receiving equipment.

P243 Take precautionary measures against static discharge.

P271 Use only outdoors or in a well-ventilated area.

P501 Dispose of contents/container to ...

P370+P378 In case of fire: Use ... for extinction.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**Contains:**

acetone,propan-2-one,propanone

butanone,ethyl methyl ketone

ethyl acetate

**2.3 Other hazards.**

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.**


**3.1 Substances.**

Not Applicable.

**3.2 Mixtures.**

Substances posing a danger to health or the environment in accordance with the Hazardous Substances Directive 67/548/EEC or Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification Regulation (EC) No 1272/2008	(*)Classification Directive 67/548/CEE

	<b>MATERIAL SAFETY DATASHEET</b>		Reference	FS ADSUPM in
			Date	19/01/15
			Revision	2
			Page	3 of 14
<b>Code:</b>	<b>ADSUPM</b>	<b>Denomination</b>	<b>CHEMICAL ADHESIVE CARTRIDGE</b>	

Index No: 606-001-00-8 CAS No: 67-64-1 EC No: 200-662-2 Registration No: 01-2119471330-49-XXXX	[1] acetone,propan-2-one,propanone	10 - 15 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336	F Xi R11 R36 R66 R67
Index No: 606-002-00-3 CAS No: 78-93-3 EC No: 201-159-0 Registration No: 01-2119457290-43-XXXX	[1] butanone,ethyl methyl ketone	2.5 - 15 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336	F Xi R11 R36 R66 R67
Index No: 607-022-00-5 CAS No: 141-78-6 EC No: 205-500-4 Registration No: 01-2119475103-46-XXXX	[1] ethyl acetate	2.5 - 15 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336	F Xi R11 R36 R66 R67

(\* ) The complete text of the R and H phrases is given in section 16 of this Safety Data Sheet.

[1] Substance with a Community workplace exposure limit (see section 8.1).

## SECTION 4: FIRST AID MEASURES.

### 4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

#### Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

#### Eye contact.

If wearing contact lenses, remove them. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.


#### Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. **NEVER** use solvents or thinners.

#### Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. **NEVER** induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed.

	<b>MATERIAL SAFETY DATASHEET</b>		Reference	FS ADSUPM in
			Date	19/01/15
			Revision	2
			Page	4 of 14
<b>Code:</b>	<b>ADSUPM</b>	<b>Denomination</b>	<b>CHEMICAL ADHESIVE CARTRIDGE</b>	

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate. Can cause allergic reactions.

#### 4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

### SECTION 5: FIREFIGHTING MEASURES.

The product is Highly inflammable, it can cause or considerably worsen a fire, the necessary prevention measures should be taken and risks avoided. In case of fire, the following measures are recommended:

#### 5.1 Extinguishing media.

##### Recommended extinguishing methods.

Extinguisher powder or CO<sub>2</sub>. In case of more serious fires, also alcohol-resistant foam and water spray. Do not use a direct stream of water to extinguish.

#### 5.2 Special hazards arising from the mixture.

##### Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

#### 5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

##### Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and gloves.

### SECTION 6: ACCIDENTAL RELEASE MEASURES.

#### 6.1 Personal precautions, protective equipment and emergency procedures.


Eliminate possible ignition points and ventilate the area. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

#### 6.2 Environmental precautions.

Prevent the contamination of drains, surface or subterranean waters, and the ground.

#### 6.3 Methods and material for containment and cleaning up.

Pick up the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomite, etc.). Pour the product and the absorbent in an appropriate container. The contaminated area should be immediately cleaned with an appropriate de-contaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

	<b>MATERIAL SAFETY DATASHEET</b>		Reference	FS ADSUPM in
			Date	19/01/15
			Revision	2
			Page	5 of 14
Code:	ADSUPM	Denomination	CHEMICAL ADHESIVE CARTRIDGE	

#### 6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

## SECTION 7: HANDLING AND STORAGE.

### 7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8. Never use pressure to empty the containers. They are not pressure-resistant containers.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Keep the product in containers made of a material identical to the original.

### 7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 35° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

Classification and threshold amount of storage in accordance with Annex I to Directive 2012/18/EU (SEVESO III)::

Code	Description	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
P5b	FLAMMABLE LIQUIDS	50	200


### 7.3 Specific end use(s).

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

### 8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m <sup>3</sup>
acetone,propan-2-one,propanone	67-64-1	European Union [1]	<b>Eight hours</b>	500	1210
			<b>Short term</b>		
		United Kingdom [2]	<b>Eight hours</b>	500	1210
			<b>Short term</b>	1500	3620
butanone,ethyl methyl ketone	78-93-3	European Union [1]	<b>Eight hours</b>	200	600
			<b>Short term</b>	300	900
		United	<b>Eight hours</b>	200	600

	<b>MATERIAL SAFETY DATASHEET</b>		Reference	FS ADSUPM in
			Date	19/01/15
			Revision	2
			Page	6 of 14
<b>Code:</b>	<b>ADSUPM</b>	<b>Denomination</b>	<b>CHEMICAL ADHESIVE CARTRIDGE</b>	

ethyl acetate	141-78-6	Kingdom [2]	<b>Short term</b>	300	899
		United Kingdom [2]	<b>Eight hours</b>	200	
			<b>Short term</b>	400	

[1] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

[2] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adopted by Health and Safety Executive.

The product does NOT contain substances with Biological Limit Values.  
Concentration levels DNEL/DMEL:


Name	DNEL/DMEL	Type	Value
acetone,propan-2-one,propanone N. CAS: 67-64-1 N. CE: 200-662-2	DNEL (Workers)	Inhalation, Long-term, Systemic effects	1210 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Long-term, Systemic effects	200 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Acute, Local effects	2420 (mg/m <sup>3</sup> )
	DNEL (Workers)	Dermal, Long-term, Systemic effects	186 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	62 (mg/kg bw/day)
	DNEL (General population)	Oral, Long-term, Systemic effects	62 (mg/kg bw/day)
butanone,ethyl methyl ketone N. CAS: 78-93-3 N. CE: 201-159-0	DNEL (Workers)	Inhalation, Long-term, Systemic effects	600 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Long-term, Systemic effects	106 (mg/m <sup>3</sup> )
	DNEL (Workers)	Dermal, Long-term, Systemic effects	1161 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	412 (mg/kg bw/day)
	DNEL (General population)	Oral, Long-term, Systemic effects	31 (mg/kg bw/day)
	DMEL (General population)	Inhalation, Long-term, Systemic effects	106 (mg/m <sup>3</sup> )
	DMEL (General population)	Dermal, Long-term, Systemic effects	412 (mg/m <sup>3</sup> )
ethyl acetate N. CAS: 141-78-6 N. CE: 205-500-4	DNEL (Workers)	Inhalation, Long-term, Systemic effects	734 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Long-term, Local effects	734 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Long-term, Local effects	367 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Acute, Local effects	1468 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Acute, Local effects	734 (mg/m <sup>3</sup> )
	DNEL (Workers)	Dermal, Long-term, Systemic effects	63 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	37 (mg/kg bw/day)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
acetone,propan-2-one,propanone N. CAS: 67-64-1 N. CE: 200-662-2	aqua (freshwater)	10,6 (mg/L)
	aqua (marine water)	1,06 (mg/L)
	aqua (intermittent releases)	21 (mg/L)
	PNEC STP	100 (mg/L)
	sediment (freshwater)	30,04 (mg/kg sediment dw)
	sediment (marine water)	3,04 (mg/kg sediment dw)

	<b>MATERIAL SAFETY DATASHEET</b>		Reference	FS ADSUPM in
			Date	19/01/15
			Revision	2
			Page	7 of 14
<b>Code:</b>	<b>ADSUPM</b>	<b>Denomination</b>	<b>CHEMICAL ADHESIVE CARTRIDGE</b>	




	PNEC soil	29,5 (mg/kg soil dw)
butanone,ethyl methyl ketone N. CAS: 78-93-3 N. CE: 201-159-0	aqua (freshwater)	55,8 (mg/L)
	aqua (marine water)	55,8 (mg/L)
	Soil	22,5 (mg/kg soil dw)
	aqua (intermittent releases)	55,8 (mg/L)
	PNEC STP	709 (mg/L)
	sediment (freshwater)	284,74 (mg/kg sediment dw)
	sediment (marine water)	284,7 (mg/kg sediment dw)
	oral (Hazard for predators)	1000 (mg/kg food)
ethyl acetate N. CAS: 141-78-6 N. CE: 205-500-4	aqua (freshwater)	0,24 (mg/L)
	aqua (marine water)	0,024 (mg/L)
	aqua (intermittent releases)	1,65 (mg/L)
	sediment (freshwater)	1,15 (mg/L)
	sediment (marine water)	0,115 (mg/L)
	Soil	0,148 (mg/kg soil dw)
	PNEC STP	650 (mg/L)
	oral (Hazard for predators)	0,2 (g/kg food)


PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.



## 8.2 Exposure controls.

### Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

<b>Concentration:</b>	<b>100 %</b>		
<b>Uses:</b>			
<b>Breathing protection:</b>			
PPE:	Filter mask for protection against gases and particles.		
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.		
CEN standards:	EN 136, EN 140, EN 405		
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.		
Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.		
<b>Hand protection:</b>			
PPE:	Protective gloves against chemicals.		
Characteristics:	«CE» marking, category III.		
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420		
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.		
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.		
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.):	> 480
		Material thickness (mm):	0,35
<b>Eye protection:</b>			
PPE:	Face shield.		
Characteristics:	«CE» marking, category II. Face and eye protector against splashing liquid.		
CEN standards:	EN 165, EN 166, EN 167, EN 168		
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly.		
Observations:	Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame.		

	<b>MATERIAL SAFETY DATASHEET</b>		Reference	FS ADSUPM in
			Date	19/01/15
			Revision	2
			Page	8 of 14
<b>Code:</b>	<b>ADSUPM</b>	<b>Denomination</b>	<b>CHEMICAL ADHESIVE CARTRIDGE</b>	

Skin protection:		
PPE: Characteristics: CEN standards: Maintenance: Observations:	Anti-static protective clothing. «CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements. EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5 In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.	
PPE: Characteristics: CEN standards: Maintenance: Observations:	Anti-static safety footwear. «CE» marking, category II. EN ISO 13287, EN ISO 20344, EN ISO 20346 The footwear should be checked regularly The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different widths.	

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

### 9.1 Information on basic physical and chemical properties.

Appearance: Paste with characteristic colour and odour

Colour: N.A./N.A.

Odour: N.A./N.A.

Odour threshold: N.A./N.A.

pH: 7

Melting point: N.A./N.A.

Boiling Point: 63,85 °C

Flash point: -2 °C

Evaporation rate: N.A./N.A.

Inflammability (solid, gas): N.A./N.A.

Lower Explosive Limit: N.A./N.A.

Upper Explosive Limit: N.A./N.A.

Vapour pressure: N.A./N.A.

Vapour density: N.A./N.A.

Relative density: 1,20 g/cm<sup>3</sup>

Solubility: N.A./N.A.

Liposolubility: N.A./N.A.


Hydrosolubility: N.A./N.A.

Partition coefficient (n-octanol/water): N.A./N.A.

Auto-ignition temperature: N.A./N.A.

Decomposition temperature: N.A./N.A.



	<b>MATERIAL SAFETY DATASHEET</b>		Reference	FS ADSUPM in
			Date	19/01/15
			Revision	2
			Page	9 of 14
<b>Code:</b>	<b>ADSUPM</b>	<b>Denomination</b>	<b>CHEMICAL ADHESIVE CARTRIDGE</b>	

Viscosity: N.A./N.A.

Explosive properties: N.A./N.A.

Oxidizing properties: N.A./N.A.

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

## 9.2. Other information.

Volatile organic compound (VOC)

VOC content (p/p): 26,08 %

VOC content: **312,96** g/l

## SECTION 10: STABILITY AND REACTIVITY.

### 10.1 Reactivity.

The product does not present hazards by their reactivity.

### 10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

### 10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

### 10.4 Conditions to avoid.

Avoid any improper handling.

### 10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

### 10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

## SECTION 11: TOXICOLOGICAL INFORMATION.


**IRRITANT PREPARATION. Splatters in the eyes can cause irritation.**

### 11.1 Information on toxicological effects.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Splatters in the eyes can cause irritation and reversible damage.

**Toxicological information about the substances present in the composition.**

	<b>MATERIAL SAFETY DATASHEET</b>		Reference	FS ADSUPM in
			Date	19/01/15
			Revision	2
			Page	10 of 14
<b>Code:</b>	<b>ADSUPM</b>	<b>Denomination</b>	<b>CHEMICAL ADHESIVE CARTRIDGE</b>	

Name	Acute toxicity			
	Type	Test	Kind	Value
acetone,propan-2-one,propanone CAS No: 67-64-1      EC No: 200-662-2	Oral Dermal Inhalation	LD50	Rat	5800 (mg/kg bw)

a) acute toxicity;

Not conclusive data for classification.

b) irritation;

Product classified:

Eye irritation, Category 2: Causes serious eye irritation.

c) corrosivity;

Not conclusive data for classification.

d) sensitisation;

Not conclusive data for classification.

e) repeated dose toxicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) mutagenicity;


Not conclusive data for classification.

h) toxicity for reproduction;

Not conclusive data for classification.

## SECTION 12: ECOLOGICAL INFORMATION.

### 12.1 Toxicity.

	<b>MATERIAL SAFETY DATASHEET</b>		Reference	FS ADSUPM in
			Date	19/01/15
			Revision	2
			Page	11 of 14
Code:	<b>ADSUPM</b>	Denomination	<b>CHEMICAL ADHESIVE CARTRIDGE</b>	

Name	Ecotoxicity			
	Type	Test	Kind	Value
acetone,propan-2-one,propanone N. CAS: 67-64-1      EC No: 200-662-2	Fish	LC50	Fish	8300 (mg/l)
	Aquatic invertebrates	LC50	Crustacean	8450 (mg/l)
	Aquatic plants	EC50	Algae	7200 (mg/l)

### 12.2 Persistence and degradability.

No information is available about persistence and degradability of the product.

### 12.3 Bioaccumulative potencial.

**Information about the bioaccumulation of the substances present.**

Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level
butanone,ethyl methyl ketone N. CAS: 78-93-3      EC No: 201-159-0	0,29	-	-	Very low
ethyl acetate N. CAS: 141-78-6      EC No: 205-500-4	0,73	-	-	Very low

### 12.4 Mobility in soil.

No information is available about the mobility in soil.  
The product must not be allowed to go into sewers or waterways.  
Prevent penetration into the ground.

### 12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

### 12.6 Other adverse effects.


No information is available about other adverse effects for the environment.

## SECTION 13 DISPOSAL CONSIDERATIONS.

### 13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

	<b>MATERIAL SAFETY DATASHEET</b>		Reference	FS ADSUPM in
			Date	19/01/15
			Revision	2
			Page	12 of 14
Code:	<b>ADSUPM</b>	Denomination	<b>CHEMICAL ADHESIVE CARTRIDGE</b>	

## SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

**Land:** Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

**Sea:** Transport by ship: IMDG.

Transport documentation: Bill of lading

**Air:** Transport by plane: ICAO/IATA.

Transport document: Airway bill.

### 14.1 UN number.

UN No: UN1325

### 14.2 UN proper shipping name.

Description: UN 1325, FLAMMABLE SOLID, ORGANIC, N.O.S., 4.1, PG III, (E)

### 14.3 Transport hazard class(es).

Class(es): 4.1

### 14.4 Packing group.

Packing group: III

### 14.5 Environmental hazards.

Marine pollutant: No

### 14.6 Special precautions for user.

Labels: 4.1



Hazard number: 40


ADR LQ: 5 kg

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-A, S-G

Proceed in accordance with point 6.

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code.

The product is not transported in bulk.

	<b>MATERIAL SAFETY DATASHEET</b>		Reference	FS ADSUPM in
			Date	19/01/15
			Revision	2
			Page	13 of 14
Code:	<b>ADSUPM</b>	Denomination	<b>CHEMICAL ADHESIVE CARTRIDGE</b>	

## SECTION 15: REGULATORY INFORMATION.

### 15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

See annex I of the Directive 96/82/EC of 9 December 1996 on the control of major-accident hazards involving dangerous substances and the Regulation (EC) No 689/2008 of the European Parliament and of the Council of 17 June 2008 concerning the export and import of dangerous chemicals and its subsequent updates.

The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): P5b

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

### 15.2 Chemical safety assessment.

There has been no evaluation a chemical safety assessment of the product.

## SECTION 16: OTHER INFORMATION.

Complete text of the R phrases that appear in section 3:

R11	Highly flammable.
R36	Irritating to eyes.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

Complete text of the H phrases that appear in section 3:

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Sections changed compared with the previous version:

9,15,16

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

### Labelling in accordance with Directive 1999/45/EC:

Symbols:



Highly flammable




Irritant

R Phrases:

R11	Highly flammable.
R36	Irritating to eyes.
R67	Vapours may cause drowsiness and dizziness.

S Phrases:

S9	Keep container in a well-ventilated place.
----	--

	<b>MATERIAL SAFETY DATASHEET</b>		Reference	FS ADSUPM in
			Date	19/01/15
			Revision	2
			Page	14 of 14
<b>Code:</b>	<b>ADSUPM</b>	<b>Denomination</b>	<b>CHEMICAL ADHESIVE CARTRIDGE</b>	

- S16                    Keep away from sources of ignition - No smoking.
- S26                    In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- S33                    Take precautionary measures against static discharges.
- S43                    In case of fire, use ... (indicate in the space the precise type of fire-fighting equipment. If water increases risk, add «Never use water»).
- S51                    Use only in well-ventilated areas.
- S60                    This material and its container must be disposed of as hazardous waste.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.